

Category	Type	Characteristic	Package	Colors	Chain No.	Pitch (mm)	Inner Width (mm)	Pin length Clip-type (mm)	Pin length Rivet-type (mm)	Plate Thickness Outer (mm)	Plate Thickness Inner (mm)
SEAL CHAIN	HEAVY-DUTY X-RING CHAIN	They are "X"-ring chains with improved durability and reduced friction loss. They are heavy duty chains with thicker plates than standard "X"-ring chains.		Standard	ES520HXC	15.875	6.35	22.3	21.2	2.20	2.20
				Gold	ES520HXCGP	15.875	6.35	22.3	21.2	2.20	2.20
				Standard	ES530HXC	15.875	9.53	26.7	25.6	2.40	2.60
				Gold	ES530HXCGP	15.875	9.53	26.7	25.6	2.40	2.60
	X-RING CHAIN	"X"-ring chains are high-performance chain with friction and long life: 1) "X"-ring chains have about 1.5 times longer wear resistance than IZUMI's "O"-ring chains. 2) About half as much the power loss as IZUMI's "O"-ring chains.		Standard	ES520XC	15.875	6.35	21.4	20.5	2.00	2.00
				Gold	ES520XCGP	15.875	6.35	21.4	20.5	2.00	2.00
				Standard	ES525XC	15.875	7.94	23.8	22.8	2.20	2.20
				Gold	ES525XCGP	15.875	7.94	23.8	22.8	2.20	2.20
	HEAVY-DUTY O-RING CHAIN ("SDC" series)	They are seal chains with improved durability. They are more durable chains with thicker plates than the standard SDC series "O"-ring chains.		Standard	ES520HSDC	15.875	6.35	22.3	21.2	2.20	2.20
				Standard	ES530HSDC	15.875	9.53	26.7	25.6	2.40	2.60
	O-RING CHAIN ("SDC" series)	They are top quality "O"-ring chains with solid seamless bushings. They are expected to last at least ten times longer than our standard type chains under appropriate maintenance.		Standard	ES520SDC	15.875	6.35	21.4	20.5	2.00	2.00
				Gold	ES520SDCGP	15.875	6.35	21.4	20.5	2.00	2.00
				Silver	ES520SDCNP	15.875	6.35	21.4	20.5	2.00	2.00
				Standard	ES525SDC	15.875	7.94	23.8	22.8	2.20	2.20
				Gold	ES525SDCGP	15.875	7.94	23.8	22.8	2.20	2.20
				Silver	ES525SDCNP	15.875	7.94	23.8	22.8	2.20	2.20
				Standard	ES530SDC	15.875	9.53	25.5	24.5	2.20	2.20
				Gold	ES530SDCGP	15.875	9.53	25.5	24.5	2.20	2.20
				Silver	ES530SDCNP	15.875	9.53	25.5	24.5	2.20	2.20
				Silver	ES630SDCNP	19.050	9.53	26.3	—	2.40	2.40
	HEAVY-DUTY O-RING CHAIN ("SDR" series)	This is a seal chain with high cost performance. This is a more durable chain with thicker plates than the standard SDR series.		Standard	ES530HSDR	15.875	9.53	26.7	25.6	2.40	2.60
				Standard	ES630SDR	19.050	9.53	26.3	—	2.40	2.40
	O-RING CHAIN ("SDR" series)	They are high performance "O"-ring chains with curled bushings and is one of more anti-wear chains in our line.		Standard	ES428SDR	12.700	7.94	19.8	18.8	1.50	1.50
				Standard	ES520SDR	15.875	6.35	21.4	20.5	2.00	2.00
Gold				ES520SDRGP	15.875	6.35	21.4	20.5	2.00	2.00	
Standard				ES530SDR	15.875	9.53	25.5	24.5	2.20	2.20	
Gold				ES530SDRGP	15.875	9.53	25.5	24.5	2.20	2.20	
Standard				ES630SDR	19.050	9.53	26.4	—	2.40	2.40	
NON-SEAL CHAIN	MOTOCROSS RACING CHAIN	520MCR II is designed exclusively for motocross.		Gold	ES520MCR II	15.875	6.35	19.0	18.0	2.00	2.00
	HEAVY DUTY CHAIN	High-class heavy duty chains are used generally for both road and off-road. They have high resistance to abrasion and tensile forces as each part is produced by using special heat treatment and special machine.		Standard	ES428H	12.700	7.94	20.00	—	2.00	2.00
				Gold	ES428HGP	12.700	7.94	20.00	—	2.00	2.00
				Standard	ES520H	15.875	6.35	20.90	—	2.40	2.40
				Standard	ES525H	15.875	7.94	22.65	—	2.40	2.40
				Standard	ES530H	15.875	9.53	24.10	—	2.40	2.40
				Standard	ES530HT	15.875	9.53	24.05	—	2.40	2.40
	STANDARD TYPE	Standard type drive chain which is under ordinary drive conditions. From the stage of material selection to the completion, production process is under IZUMI's strict quality. As for above, this type of chain is distinguished for its stabilized performance.		Standard	ES415S	12.700	4.76	15.10	—	1.50	1.50
				Standard	ES420	12.700	6.35	15.80	—	1.50	1.50
				Standard	ES428	12.700	7.94	18.10	—	1.50	1.50
				Standard	ES520	15.875	6.35	19.35	—	2.00	2.00
				Standard	ES525	15.875	7.94	20.90	—	2.00	2.00
				Standard	ES530	15.875	9.53	22.20	—	2.00	2.00
				Standard	ES630	19.050	9.53	24.00	—	2.40	2.40
Standard				ES25	6.350	3.18	7.6	—	0.75	0.75	
CAM CHAIN	Our cam chain is high quality with its excellent wear resistance and smooth power transmission at low noise levels under high rotational speed.		Standard	ES25-2	6.350	3.18	14.0	—	0.75	0.75	
			Standard	ES25H	6.350	3.18	8.6	—	1.00	1.00	